


COMPANY:				ORDER	QUOTE	Viewed Outside	Page No.: of					
TEL:		FAX:		Order Date: / /			ENERGY RATING	A	B	C		
EMAIL:				Req'd Date: / /			PAS24:	YES		NO		
REF:				Signed:								
Window Colour:	Standard Colours >>>	White PVC	White FOIL	Cream FOIL	Anthracite GREY On White	Cream FOIL On White	Fastrack Colours >>>	Agate Grey On White	Chartwell Green On White	Special Foil or RAL Spray colour	OUTSIDE	
Hardware Colour:	WHITE	GOLD	CHROME	FLAT BLACK	SATIN SILVER	GRAPHITE	BRONZE	ANTIQUA BLACK	Special Foil or RAL Spray colour			INSIDE
Spacer Bar Colour:	SILVER (aluminium)		DARK BRONZE (aluminium)		GOLD (aluminium)	BLACK WARMEDGE	GREY WARMEDGE	WHITE WARMEDGE				

VERTICAL SLIDING SASH SPEC/INFO				SIZES TO INCLUDE ALL CILLS AND ADD-ON				
Location:		Quantity:		Please indicate clearly any Add-on and Georgian bar detail				
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)		Width			
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)		DEEP RAIL (milled)		Height			
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)			Top Glass Type			
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE		Toughened	Obscure		
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE		Bottom Glass Type			
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE		Toughened	Obscure		
Trickle Vent (If required fitted to head of top sash)	YES		NO		Georgian Bar			
Weather Bar (Fitted across cill where it meets lower sash)	YES		NO		Internal (18mm)	Astragal (22mm)		
Notes 1:					Notes 2:			

VERTICAL SLIDING SASH SPEC/INFO				SIZES TO INCLUDE ALL CILLS AND ADD-ON				
Location:		Quantity:		Please indicate clearly any Add-on and Georgian bar detail				
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)		Width			
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)		DEEP RAIL (milled)		Height			
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)			Top Glass Type			
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE		Toughened	Obscure		
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE		Bottom Glass Type			
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE		Toughened	Obscure		
Trickle Vent (If required fitted to head of top sash)	YES		NO		Georgian Bar			
Weather Bar (Fitted across cill where it meets lower sash)	YES		NO		Internal (18mm)	Astragal (22mm)		
Notes 1:					Notes 2:			

VERTICAL SLIDING SASH SPEC/INFO				SIZES TO INCLUDE ALL CILLS AND ADD-ON				
Location:		Quantity:		Please indicate clearly any Add-on and Georgian bar detail				
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)		Width			
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)		DEEP RAIL (milled)		Height			
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)			Top Glass Type			
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE		Toughened	Obscure		
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE		Bottom Glass Type			
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE		Toughened	Obscure		
Trickle Vent (If required fitted to head of top sash)	YES		NO		Georgian Bar			
Weather Bar (Fitted across cill where it meets lower sash)	YES		NO		Internal (18mm)	Astragal (22mm)		
Notes 1:					Notes 2:			



COMPANY:	ORDER	QUOTE	Viewed Outside	Page No.:	of		
TEL:	FAX:	Order Date:	/ /	ENERGY RATING	A	B	C
EMAIL:	Req'd Date:	/ /	Signed:	PAS24:	YES	NO	
REF:							

GRAF WELDED VS MULTI-SEGMENT DETAIL SHEET

Window Colour:	Standard Colours >>>	White PVC	White FOIL	Cream FOIL	Anthracite GREY On White	Cream FOIL On White	Fastrack Colours >>>	Agate Grey On White	Chartwell Green On White	Special Foil or RAL Spray colour	OUTSIDE
Hardware Colour:	WHITE	GOLD	CHROME	FLAT BLACK	SATIN SILVER	GRAPHITE	BRONZE	ANTIQUÉ BLACK		Special Foil or RAL Spray colour	INSIDE
Spacer Bar Colour:	SILVER (aluminium)	DARK BRONZE (aluminium)	GOLD (aluminium)	BLACK WARMEDGE	GREY WARMEDGE	WHITE WARMEDGE					

GRAF WELDED VERTICAL SLIDING SASH SPEC/INFO

Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)	
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES	NO	
Weather Bar (Fitted across cill where it meets lower sash)	YES	NO	
Notes 1:			

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Please indicate clearly any Add-on and Georgian bar detail

Width

Split

Split

Height

Top Glass Type		Bottom Glass Type		Georgian Bar	
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astragal (22mm)

GRAF WELDED VERTICAL SLIDING SASH SPEC/INFO

Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)	
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES	NO	
Weather Bar (Fitted across cill where it meets lower sash)	YES	NO	
Notes 1:			

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Please indicate clearly any Add-on and Georgian bar detail

Width

Split

Split

Height

Top Glass Type		Bottom Glass Type		Georgian Bar	
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astragal (22mm)

GRAF WELDED VERTICAL SLIDING SASH SPEC/INFO

Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)	
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES	NO	
Weather Bar (Fitted across cill where it meets lower sash)	YES	NO	
Notes 1:			

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Please indicate clearly any Add-on and Georgian bar detail



Width

Split

Split

Height

Top Glass Type		Bottom Glass Type		Georgian Bar	
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astragal (22mm)



COMPANY:		ORDER	QUOTE	Viewed Outside	Page No.: _____ of _____		
TEL:	FAX:	Order Date: / /		ENERGY RATING	A	B	C
EMAIL:		Req'd Date: / /		PAS24:	YES		NO
REF:		Signed:					

VS BAY & WELDED CILL DETAIL SHEET

Window Colour:	Standard Colours >>>	White PVC	White FOIL	Cream FOIL	Anthracite GREY On White	Cream FOIL On White	Fastrack Colours >>>	Agate Grey On White	Chartwell Green On White	Special Foil or RAL Spray colour	OUTSIDE
Hardware Colour:	WHITE	GOLD	CHROME	FLAT BLACK	SATIN SILVER	GRAPHITE	BRONZE	ANTIQUÉ BLACK		Special Foil or RAL Spray colour	INSIDE
Spacer Bar Colour:	SILVER (aluminium)	DARK BRONZE (aluminium)		GOLD (aluminium)	BLACK WARMEDGE	GREY WARMEDGE	WHITE WARMEDGE				

VERTICAL SLIDING SASH SPEC/INFO

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)		DEEP RAIL (milled)
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES		NO
Weather Bar (Fitted across cill where it meets lower sash)	YES		NO

Please indicate clearly any Add-on and Georgian bar detail

	A Left Side	B Front	C Right Side
↑ Split			

Top Glass Type		Bottom Glass Type		Georgian Bar	
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astragal (22mm)

INTERNAL CILL SIZES, OVERALL HEIGHTS & ANGLES

Left side 'A' internal cill size
Front 'B' internal cill size
Right side 'C' internal cill size
Overall Height
Left Angle (Variable angle VS bay post 120 to 150 degrees only)
Right Angle (Variable angle VS bay post 120 to 150 degrees only)

DRAW CILL PLAN BELOW

90 DEGREE FIXED ANGLE VS BAY POST ALSO AVAILABLE

IF YOU DO NOT REQUIRE A WELDED CILL & BAY POSTS USE THE SINGLE VS OR MULTI-SEGMENT FORMS WHEN ORDERING